

PRIMARY CORNER DESCRIPTION M.C. on Rg. line, E. bdy. Sec. 1

Alias <u>883010</u>	Description <u>M.C. Right bank of Umpqua River</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 4 Page(s) 1732)

Set Post, from which
A Spicewood, 5" dia., bears N.45°E., 8 lks.
A Spicewood, 5" dia., bears N.40°W., 9 lks.

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1766)

The meander cor. on the N. side of the Umpqua River which is a post firmly set 24" above ground, from which
A Spicewood 5" dia., bears N.40°W., 9 lks. dist. mkd. T22S R11W S1 MC BT.
A Spicewood 5" dia., bears N.45°E., 8 lks. dist. mkd. T22S R10W S6 MC BT.

(At the request of the Surveyor General of Oregon to the District Forester, the cor. reestablished by Maxwell in 1914 of the tsp. cor. for T22S Rgs. 10 & 11 be proven to be the authentic old corner. In examining that corner, the M.C. to the south was visited) Resurvey by Frederick W. Rase, Surveyor - Forest Service - Survey commenced Sept. 11, 1915 and approved April 16, 1915. (DCSO records, Vol 28 Pages 11996-97)

Right bank of Umpqua River. I make diligent search for meander cor. but fail to find any trace of it. (Settlers in the neighborhood claim private surveyors had searched for it a number of times during the past ten years but never found it.) From this point the N. end of old fence on S. bank of Umpqua River, supposed to have been built on the range line years ago, bears South.
I reestablish the meander cor. as follows:
Set a sandstone 30 x 15 x 10", 23" in the ground, over a stone marked with a cross, marked MC on side facing the river; and 6 grooves on E. and W. faces; from which
An Alder 10" dia., bears East, marked T22S R10W S6 MC BT.
A sandstone boulder embedded ins teep S. side hill, 15 x 15 x 10 ft. high, bears N.49°30'W., 54 lks. dist., mkd. X BR on SE. face.

(Cont. Next Page)

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 700642

PRIMARY CORNER DESCRIPTION M.C. on Rg. line, E. bdy. Sec. 1

Alias <u>883010</u>	Description <u>M.C. Right bank Umpqua River</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by James W. Prochnau PLS #1305 - For: U.S. Forest Service - Aug. 1985 - M 99-21 A&B

WITNESS CORNER

Set 3¼" USFS alum. cap with magnet on a 1½" x 30" alum. pipe with flared base. Cap properly marked and with PLS #1305. Cap and pipe bears N.0°39'52"E., 23.26 ft. on line from true position.

New BTs -34" D.Fir bears S.21°E., 10.5 ft. scribed X BT.
10" Maple bears N.16°W., 7.8 ft. scribed X BT.