

PRIMARY CORNER DESCRIPTION HES # 213 COR #7

| Alias | Description |
|-------|-------------|
|       |             |
|       |             |
|       |             |
|       |             |

Orig. Homestead Entry Survey No. 213 - Entryman: Leonard Fletcher Wilson - H.E. No. 09836, dated Nov. 13, 1914 (DCSO records Vol. 28 Page(s) 12080)

-----  
Mon. Set- 24x12x6", 14" in the ground, over a stone marked with a cross for cor. #7 of this survey, marked 7 H E S 213 on side facing the claim.

Accessories Set-  
No Bearings available dig pits 24x24x12" crosswise on line south west and west of corner, 7' and raise a mound of earth, 4' base 2' high 3½' within the claim.  
Cor. #6 of tract A of this survey, bears east 31 lks.

-----  
Douglas County Surveyors Office - Randall Smith & Stephen Flause - April 3, 1997 - C.S. 64/74-15

-----  
Mon. Fd.- 20"x12"x6" stone no mark found 2½' below ground Orig. corner. Orig. Rec. 24"x12"x6" marked stone.

Accessories Fd.- Orig. 4" now 36" dia. 15' high spruce snag OBT for HES #6, bears N.85°E., 24' (agrees with calc. rec. ) OBT to cor. #6.  
Orig 10" now clump of 3 13" dia. young ashes root crown bears N.56½°W., 117.7' (agrees with calc. rec.) Obt to cor. # 6.

Mon. Set- 5/8"x5' Iron rod with alum. cap stamped "NO7 1997" is set 8" below ground. This position is determined by found stone corroborated by evidence found at HES Cor #6. Orig. stone is laid along north edge 2½' below ground.

New Accessories -  
29" Ash marked for HES Cor #6 "X6 HES 213 MC CS BT" on a double blaze, bears N.60°W., 125' (BT tag refers to cor. #6)  
9" Holly bark scribed for HEW Cor #6 "X BT", bears south 109.4' (BT tag refers to cor. #6)  
Power Pole "9-140", bears S.39°E., 160.8'.

-----  
Found OK by R. Ward, Mar. 2001 - M136-61