

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T22-13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #68 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 1987)

Set post cor. of secs. 25, 30, 31 and 36, from which
A Dwarf Pine 4" dia., bears N.66°W., 37 lks. dist.
A Dwarf Pine 6" dia., bears S.75°W., 49 lks. dist.
A Dwarf Pine 7" dia., bears S.5°E., 57 lks. dist.
A Red Fir 6" dia., bears N.28°E., 9 lks. dist.

GL0 survey by Simon B. Cathcart, Deputy Surveyor, under Contract #559, dated Nov. 15, 1890 - (DCSO records Vol. 5 Page(s) 2077)

Post entirely rotted. I found the bearing trees all standing as follows, viz:

A Dwarf Pine 6" dia., bearing N.66°W., 37 lks. dist. mkd.
T22S R13W S25 BT.
A Dwarf Pine 7" dia., bearing S.75°W., 49 lks. dist. mkd.
T22S R13W S36 BT.
A Dwarf Pine 10" dia., bearing S.5°E., 57 lks. dist. mkd.
T22S R12W S31 BT.
A Red Fir 6" dia., bearing N.28°E., 9 lks. dist. mkd. T22S
R12W S30 BT.

The Fir is dead, all the other bearing trees are green. I set a Pine post, 4" sq., 4½ ft. long, 2 ft. in ground mkd. T22S S30 on NE.; R12W S31 on SE.; R13W S36 on SW.; and S25 on NW. faces, with 1 notch on S. and 5 notches on N. edges.

Douglas Co. Surveyors Office - James Byron, Deputy - Ray Irving; A. West; F.C. Cox; John Fee, crew - March 3, 1955 - C.S. File 46/110 and M 7-12

Found - 1¼" Axle, 1 ft. above ground.
A 12" Pine bears S.71°E., 15.7 ft., knife scribed "31 BT".
A 12" Pine bears S.68°W., 33.8 ft., knife scribed "30 BT"
Bottom of old Pine stump S.5°E., 37.6 ft. (Checks for original BT.)
Bottom of old Pine stump N.28°E., 5.9 ft. (Checks for original BT.)
Blazed and scribed four new BTs:
6" Pine N.12°W., 15.5 ft. "R13W S25 CS BT"
6" Pine S.47°W., 47.4 ft. "R13W S36 CS BT"
7" Pine S.8½°E., 26.3 ft. "R12W S31 CS BT"
7" Pine N.37°E., 13.6 ft. "R12W S30 CS BT"

(Cont. Next Page)

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T22-13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. axle and 2 BTs, Feb. 1971 by Bob Kischell, Land Dept.
(Axle loose in ground sand.) (No DCSO record number)

Fd. OK, Aug. 1973, V.R.T. DCSO - C.S. File 56/35-4 pg 2
Fd. OK, Feb. 12, 1975, L.E.M., DCSO - C.S. File 59/46-35

BLM resurvey by Glenn Goodson, Rick Tawney and Elma Jean Acuna, Cadastral Surveyors - under Group #1122, surveyed Oct. 1982 - (DCSO records Vol. 44 Page(s) 17060-61)

The Sec. cor., monumented with a 1¼" axle, firmly set, projecting 1 ft. above the ground. DCSO records show that in 1955, Byron found this monument to be properly related to two original bearing trees which no longer exist. It is accepted as the best available evidence of the original corner, from which the remains of the bearing trees mkd. by Byron in 1955:

A Pine 7" dia., bears N.37°E., 36 lks. dist. with scribe marks R12W S30 CS BT visible on partially healed blaze.

A Pine 10" dia., bears N.12°W., 24 lks., dist. with scribe marks R13W S25 CS BT visible on partially healed blaze.

and a tree mkd. by person(s) unknown:

A Pine 18" dia., bears S.71°E., 24 lks. dist. mkd. with a healed blaze.

At the corner point

Set an alum. post, 28" long, 2 1/2" dia., 24" in the ground, with alum. cap mkd:

T 22 S
R 13 W R 12 W
S 25 | S 30
S 36 | S 31
1982

from which a new bearing tree and a bearing object:

A Fir 10" dia., bears S.10½°E., 38½ lks. dist. mkd. T22S R12W S31 BT.

The NE. cor. of an A frame house, bears S.64¼°W., 68 lks. dist., long side bears W.

Deposit the axle inside the alum. post.

Survey by William Shull LS #909 For: U.S.F.S. - Jan. 20, 1985 - M 98-70

Found - 1982 BLM alum. cap and pipe.
7" Pine, dead, N.37°E., 23.8 ft. scribed "R12W S30 CS BT"

10" Pine N.12°W., 15.8 ft. scribed R13W S25 CS BT"

18" Pine S.71°E., 15.8 ft., healed blaze.

10" Fir S.10½°E., 25.4 ft. scribed "T22S R12W S31 BT"

(Cont. Next Page)

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. cor. for 30 & 31; 25 & 36, T22-13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

NE cor. of A-Frame house bears S.64¼°W., 44.9 ft., not scribed.
New BT - 5" Fir N.54°E., 13.2 ft. scribed "X BT"
Set USFS alum. reference monument, a 2½" x 30" alum. pipe with 3¼" alum. cap with magnet attached under cap. Cap stamped "T22S R13W R12W RM S 82°23'E 54.8' 1984 LS 909" and an arrow pointing to corner.

Fd. OK, Dec. 1989 by H. Wilcox - M 109-50
Fd. OK, April 1996 by D.Jones - 1996-0111 A&B
Fd. OK by B. Bacon, Feb. 2001 - M136-58
FD. OK by T Hostetter, July 2012 - M164-11
FD Alum cap & BTs per 1982 BLM, J Estabrook, 2/2017 2017-0027A-B