

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 113300

PRIMARY CORNER DESCRIPTION M C So. bdy. Sec. 19

Alias 801900 Description MC northerly bdy arm of Clear Lake
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Simon B. Cathcart, Deputy Surveyor, under Contract #559, dated Nov. 15, 1890 - (DCSO records Vol. 5 Page(s) 2072-73)

Marked a Fir 30" dia., for meander corner for fractional Secs. 19 and 30, M C on East; T22S S19 on North; R12W on W; and S30 on South sides, from which

A Fir 8" dia., bears N.30°E., 11 lks. dist. mkd. T22S R12W S19 MC BT.

A Spruce 40" dia., bears S.65°W., 15 lks. dist. mkd. T22S R12W S30 MC BT.

Douglas County Surveyors Office - Ed. Monrean and John Powell, crew - Oct. 2, 1973 - C.S. File 56/39-1

Found - 30" Fir snag corner tree, bark scribe visible "MC" and other scribe marks.

40" now 55" Spruce, S.65°W., 9.9 ft., shows scar.
No trace of NE bearing tree.

Set Brass cap alongside SE side of corner tree marked:
County Surveyors Office

T22S R12W
S 19
M.C. S 30
1973

New BT - 40" Spruce N.52°E., 30.6 ft. scribed "T22S R12W S19 M.C. CS BT"

This corner lies on E. side of ridge (orig. call 24.43 chs.)
Also lies approx. 15 ft. above lake.