

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 129300

PRIMARY CORNER DESCRIPTION F. MC S. bdy Sec. 19

| | |
|---------------------|-------------------------------------|
| Alias <u>801990</u> | Description <u>F. MC Clear Lake</u> |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GL0 survey by Simon B. Cathcart, Deputy Surveyor, under Contract #559, dated Nov. 15, 1890 - (DCSO records Vol. 5 Page(s) 2072)

Intersect arm of Clear Lake and set Cedar post, 4" sq., 4 ft. long, 2 ft. in ground for meander corner for fractional sections 19 and 30, marked M C on West; T22S S19 on North; R12W on East; S30 on South faces, from which
A Cedar 8" dia., bears S.57°E., 18 lks. dist. mkd. T22S R12W S30 MC BT.
A Fir 30" dia., bears N.14°W., 30 lks. dist. mkd. T22S R12W S19 MC BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, and J. Isgro, Land Dept., crew - Aug. 16, 1973 - C.S. File 56/35-1

Found - 3/4" Iron pipe set by Menash in March 1973, at point for most Easterly meander corner.
Orig. 8" now 16" Cedar S.57°E., 11.9 ft., previously opened, no scribe found, blaze decayed. We rescribe "M.C. T22S R12W S30 CS BT" alongside old scribe.
We Do Not Set Brass Cap. 3/4" I.P. set for corner lies about 6 ft. from water's edge.

Fd. OK, Feb. 20, 1975 by L Monrean, DCSO - C.S. File 59/46-71

Fd. OK, Nov. 1992 by J. Minor - M 116-11