

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 30

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 2005)

Set ¼ sec. post, from which
 An Alder 12" dia., bears S.42°W., 8 lks. dist.
 An Alder 12" dia., bears N.38°E., 29 lks. dist.
(Point of Lake BonaWhawhan bears S.60°W., 4 chs. dist.)

GLO survey by Simon B. Cathcart, Deputy Surveyor, under Contract #559, dated Nov. 15, 1890 - (DCSO records Vol. 5 Page(s) 2071-72)

I find the corner to ¼ section.
I find an Alder 15" dia., plainly marked ¼ S BT on SW. side, from which I run S.38°W., 29 lks. to place ¼ section. Could find no post. The Alder bearing S.42°W., 8 lks. has fallen but the ¼ S is still visible on the trunk.
I set an Alder post 4" sq. 4 ft. long, 2 ft. in ground, marked ¼ S on NW. face.

Douglas County Surveyors Office - James W. Byron, Surveyor - C.S. File 56/35-1 - Aug. 16, 1973

Corner searched for, not found. No alders in the area are old enough or large enough to have been 15" dia. in 1891.

Survey by John Minor - For: Menasha Corp. - Nov. 1992 - M 116-11

Set 1" x 36" I.P. with 2" brass cap stamped T22S R12W ¼ S19|S30 1992 LS 2052. (Set by proportion.)
New BTs -18" Alder N.77°W., 14.7 ft. bark scribed ¼ S19 BT.
 30" Spruce S.83°W., 43.1 ft. scribed ¼ S30 BT.
 19" Alder S.17°E., 35.4 ft. bark scribed ¼ S19 BT.
 29" Spruce N.22°E., 40.3 ft. scribed ¼ S19 BT.
A Creek, S.17°E., 28.0 ft. flows S.73°W.

Fd. OK by B. Bacon, June 1999 - M131-77 cont. next page

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 30

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- 9/13-2005 - C.S. File 67/13-2 & M148-67

Found - 2" dia., brass cap on rusted 1" dia., iron pipe,
projects 2" above ground, (properly marked)

Note - The purpose of this report is to redefine the
distances to BTs as recorded by Minor (M116-11)
His distances were measured to a large spike set
in the face of the blaze - not side center - we
also noticed differences in record bearings

BTs fd - 18" alder still 18", bark scribe visible "¼ S19 BT"
bears N.79°W., 15.6 ft. (rec. N.72°W., 14.7 ft.)
30" spruce now 31" healed single blaze visible bears
S.80½°W., 44.1 ft. (Rec. S.83°W., 43.1 ft.)
19" alder now 21" bark scribe visible "¼ S30 BT"
bears S.20½°E., 36.5 ft. (rec. S.17°E., 35.4 ft.)
29" spruce now 34" partially healed single blaze
w/illegible scribe visible, bear N.22°E., 41.3
ft. (rec. N.22°E., 40.3 ft)

Note - Corner lies on moderate west facing slope. Very
brushy!
Compass decl. 16¾°E.