

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 1998)

Set ¼ sec. post, from which
A Spruce 15" dia., bears N.7°W., 20 lks. dist.
A Spruce 15" dia., bears S.30°W., 34 lks. dist.

Douglas County Surveyors Office - Janet Lundeen, Deputy - R. Smith & S. Flause, crew - C.S. File 62/43-A and M 101-18

Found - Orig. 15" dia. Spruce now 27", 5 ft. high stump with partial scribing "1/4S" bears N.7°W., 13.2 ft. (Rec. per Gordon 1857 survey)
Orig. 15" dia. Spruce now 30", 4 ft. high stump with partial scribing "1/4S" bears S.30°W., 22.4 ft. (Per rec.)

We find record bearings and distances fit well and Set a 2 3/8" Brass cap on 1¼" I.D. Iron pipe, 32" long protruding 6" above ground and stamped:

Douglas County Surveyors Office
T 22 S R 12 W
¼ S 7
S 18
1986

New BTs -17" Spruce bears N.51°E., 20.4 ft. with double blaze and scribed "¼ S7 CS BT"
8" Alder bears N.50°W., 4.5 ft. and bark scribed "CS ¼ S7 BT"
18" Spruce bears S.69½°W., 8.4 ft. with double blaze and scribed "¼ S18 CS BT"
16" Spruce bears S.2°E., 13.0 ft. with double blaze and scribed "¼ S18 CS BT"

Cor. approx. 100 ft. East of top of ridge, as calls indicate.

Fd. OK by McLind, June 1998 - M 128-75