

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCS0 records Vol. 5 Page(s) 1999)

Set ¼ sec. post, from which
A Spruce 12" dia., bears S.81°W., 7 lks. dist.
A Spruce 12" dia., bears N.31°E., 18 lks. dist.

Arthur Boyer, D.C.S - Wit: N.E. Richardson and Chas. Clark -
Nov. 9, 1936 - M 1-65

Set from initial point Winchester Bay Townsite, set by Gene Robinson, and from stumps of Spruce trees which check close, could find no signs of scribed blazes.
Set 1½" x 36" galv. Iron pipe on W. side of draw, from which
Orig. BT, 40" stump bears N.30°E., 11.9 ft. to 12" dia.
Orig. BT stump 40" bears S.81°W., 4.6 ft. Marked.
6" Alder which bears S.89°30'W., 8.1 ft. ¼ S6 CS BT.
48" Spruce stump which bears S.29°E., 9.2 ft. mkd. ¼ S7 CS BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, E. West, crew - June 1967 - C.S. File 54/46-6

Found - 2" I.P. and BT as recorded by Boyer
40" Spruce stump, badly decayed S.29°E., 9.2 ft.
(face) scribe marks visible.
New BTs -6" Spruce S.80°E., 11.0 ft. mkd. ¼ S7 CS BT.
14" Alder N.1°W., 12.3 ft. mkd. ¼ S6 CS BT.
No trace of Boyer's SW BT.
This corner lies 8.0 ft. N.81°W. of old fence corner, fences S. and E. and easterly slope ridge.

Douglas Co. Surveyors Office - Karen Reed and John Powell, crew - Sept. 7, 1982 - C.S. File 62/1-17

Found - 2" dia. Iron pipe protruding 6" above ground. (Rec. 1½" dia. per 1936)
40" Spruce stump with visible scribe bears S.29°E., 9.2 ft.
6" Spruce now 9", bears S.80°E., 11.0 ft. with a well healed double blaze.
14" Alder now 16" bears N.1°W., 12.3 ft. with visible scribe "¼ S6 CS BT" in a double blaze.
No original trees found.
New BTs -7" Spruce bears N.57°W., 19.4 ft. scribed "¼ S6 CS BT" in a double blaze.
17" Spruce bears S.37°W., 48.5 ft. scribed "¼ S7 CS BT" in a double blaze. (Cont. Next Page)

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Corner falls 3.0 ft. from old fence corner. Fence running E and S. approx. 10 ft. West of swamp and 200 ft. North of trailer park on easterly slope.

Found OK by T. Hoshall, May 2003 - M142-40
Fd OK by K DeGroot - March 2021 - M178-25

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 8/20/2025 - C.S. File 67/61-16

Found - 2" I.D. Iron pipe 6" above ground.
Very rotted 36"x6ft spruce stump S.29°E 9.2ft
12" spruce S.80°E. 11.2ft (Rec 11.0) fully healed
double blaze. Add 3½" mag nail right side center.
Very rotted 20"x1½ft alder stump N.1°W. 12.3ft
24" spruce N.57°W. 19.0ft (Rec 19.4ft) fully healed
double blaze, add 3½" mag nail right side center.
Rotted 26"x2½ft spruce stump S.37°W. 48.5ft
Steel fence post north 0.3ft
Record fence gone.
New - 25" spruce N.31°E 18.5ft scribed "T22S R12W S6 BT"
on double blaze.
16" hemlock S.62°W 6.4ft scribed "T22S R12W S7 BT"
on double blaze.
Compass decl. 14¼°E.
Trimble GEO XT Position
43°40'58.541" N.
124°10'27.111" W.