

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; and 31 of T21-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1261-62)

Set qr. sec. post, from which
A Spruce 18" dia., bears S.50¼°W., 206 lks. dist.
A Pine 6" dia., bears N.26½°E., 302 lks. dist.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre, Scott R. McMullen, Cadastral Surveyors - under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17186-87)

Point for the ¼ sec. cor. of secs. 6 and 31, at record distance; there is no remaining evidence of the original corner.

Set an alum. rod, 13 ft. long, 5/8" dia., 12 ft. in the ground, in concrete, with alum. cap mkd: T 21 S R 12 W

1/4 S 31
S 6
T 22 S
1981

No suitable trees available within limits.
Set a steel fence post alongside aluminum rod.