

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 153100

PRIMARY CORNER DESCRIPTION M.C. on So. bdy. Sec. 31

Alias <u>818210</u>	Description <u>M.C. East bdy. West Arm Eel Lake</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Simon B. Cathcart, Deputy Surveyor, under Contract #559, dated Nov. 15, 1890 - (DCSO records Vol. 5 Page(s) 2067)

-----  
Intersect West arm of Eel Lake and set a Cedar post, 4x6" 5 ft. long, 2 ft. in the ground for meander corner for fractional secs. 6 and 31, marked MC on West, T22S S31 on North; R12W on East; and T23S S6 on South faces, from which  
A Spruce 30" dia., bears S.82°E., 35 lks. dist. mkd. T23S R12W S6 MC BT.  
A Spruce 15" dia., bears N.6°W., 20 lks. dist. mkd. T22S R12W S31 MC BT.

Survey by Harvey Wilcox, LS #2244 - For: Oregon Dept. of Fish and Wildlife and Douglas County - Dec.1989 - M 109-50

-----  
Found - Orig. BT, a rotten Spruce stump, no marks, bears N.16°W., 13.2 ft.  
Orig. BT, a rotten Spruce stump, no marks, bears S.80°E., 23.1 ft.  
Set a 3/4" x 30" I.Rod with 2" alum. cap in orig. position.  
New BTs -A 36" D.Fir scribed "MC S31 BT" with an X at BH and tagged, bears N.30°E., 22.2 ft.  
A 24" D.Fir scribed "MC S6 BT" with an X at BH and tagged, bears S.2°W., 3.6 ft.