

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION C C for Secs. 31 and 32 (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Simon B. Cathcart, Deputy Surveyor, under Contract #559, dated Nov. 15, 1890 - (DCSO records Vol. 5 Page(s) 2080)

At a point 12.40 chs. West of corner to 5 and 6,
Set an Alder post, 4" sq. 5 ft. long, 2 ft. in ground for closing corner to secs. 31 and 32, marked CC T22S R12W on North; S31 on Wst; and S32 on East, with 1 notch on West and 5 notches on East faces, from which
A Fir 24" dia., bears N.16½°W., 40 lks. dist. mkd. T22S R12W S31 BT.
A Spruce 36" dia., bears N.85°E., 43 lks. dist. mkd. T22S R12W S32 BT.
A Fir 18" dia., bears S.50°E., 35 lks. dist. mkd. T22S R12W CC S31 & 32.

Survey by Harvey Wilcox, LS #2244 - For: Oregon Dept. of Fish and Wildlife and Douglas County - Dec.1989 - M 109-50

Found - Orig. BT, a Fir stump with visible scribe bears N.16°W., 26.4 ft.
Orig. BT, a Fir stump with visible scribe bears S.50°E., 23.1 ft.
Set a 3/4" x 30" I.Rod with 2" alum. cap at the orig. position, from which new BTs:
A 26" D.Fir scribed "T22S R12W S1 CC BT" with an X at BH and tagged bears N.49°W., 16.1 ft.
A 15" Alder bark scribed "T22S R12W S32 CC BT" with an X at BH and tagged bears N.37°E., 28.4 ft.
A 10" Cedar with an X at BH bears S.20°W., 2.2 ft.

fd. Ok by Jerry Estabrook 8/2010 - M161-13 A&B