

PRIMARY CORNER DESCRIPTION Sec Cor for 17, 18, 19 and 20

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 2004)

Set post corner of secs. 17, 18, 19 and 20, from which
An Alder 24" dia., bears N.59°W., 26 lks. dist.
An Alder 24" dia., bears S.60°E., 10 lks. dist.
A Hemlock 24" dia., bears N.19°E., 60 lks. dist.
A Spruce 48" dia., bears S.11°W., 154 lks. dist.

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2050)

The post being gone, I restore cor. by setting a Spruce post, 4 ft. long, 4" sq. 24" in the ground, marked T22S S17 on NE.; R12W S20 on SE.; S19 on SW. face, S18 on NW. faces, with 3 notches on S. and 5 notches on E. edges, from which
A Hemlock 24" dia., bears N.19°E., 60 lks. dist. mkd. T22S R12W S17 BT.
An Alder 24" dia., bears S.60°E., 10 lks. dit. mkd. T22S R12W S20 BT.
A Spruce 48" dia., bears S.11°W., 154 lks. dist. mkd. T22S R12W S19 BT.
An Alder 24" dia., bears N.59°W., 26 lks. dist. mkd. T22S R12W S18 BT.
in accordance with the description given in the field notes furnished me.

Douglas County Surveyors Office - James W. Byron, Surveyor - C.S. File 56/35-3 pg 2 - Aug. 14, 1973

Corner searched for, not found. Did find old brushing N & S.

Douglas County Surveyors Office - Janet Lundeen, Deputy - R. Smith and S. Flause, Crew - Sept/Dec. 1986 - C.S. 62/43-H and M 101-18

Found - 48" Spruce now 58" stump 7 ft. high with scribing "S 2" bears S.11°W., 101.6 ft. (record)
24" Hemlock now a 36" badly rotted stump 2 ft. high bears N.23½°E., 39.6 ft. (Rec. N.19°E., 39.6 ft.)
No trace of 24" Alder at S.60°E., 6.6 ft.
Depression at N.59°W., 17.2 ft. possible stump hole of orig. NW Alder.
Corner set at record bearing and distance from the 58" Spruce stump. This position agreed with record bearing and distance to the 36" badly rotted stump whose center could not easily be determined. (Cont. Next Page)

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec Cor for 17, 18, 19 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

SET 2½" brass cap on 2 3/8" O.D. x 32" Pipe. Cap mkd:
Douglas County Surveyors Office

T 22 S
S 18 | S 17
S 19 | S 20
R 12 W

1986

New BTs -19" Spruce, double blazed and scribed "T22S R12W S20
CS BT" bears S.21°E., 19.3 ft.
24" Spruce, double blazed and scribed "T22S R12W S18
CS BT" bears N.25½°W., 20.6 ft.
20" D.Fir, double blazed and scribed "T22S R12W S19
CS BT" bears S.78°W., 32.0 ft.
28" Spruce, double blazed and scribed "T22S R12W S17
CS BT" bears N.10½°E., 22.1 ft.

Fd. OK by B. Bacon, June 1999 - M131-77