

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 200420

PRIMARY CORNER DESCRIPTION So. 1/16 cor. betw. secs. 17 & 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas County Surveyors Office - Janet Lundeen, Deputy - R. Smith and S. Flause, Crew - Sept/Dec. 1986 - C.S. 62/43-I and M 101-18

-----  
Set a 2 3/8" dia. brass cap mkd: Douglas County Surveyors  
Office  
T 22 S  
R 12 W  
S 1/16 S18 | S17  
1986

on a 1" dia. (1 1/4" O.D.) x 32" long galv. I.P. firmly set and protruding 6" from ground.

New BTs - 6" dia. Spruce, double blazed and scribed "S 1/16 S12 CS BT" bears N.27°E., 40.3 ft.

12" dia. Alder double blazed and scribed "S 1/16 S18 CS BT" bears S.60 1/4°W., 16.8 ft.

14" dia. D.Fir double blazed and scribed "S 1/16 S18 CS BT" bears S.15 1/2°W., 16.7 ft.

Monument is located approx. 100 ft. North of and 20 ft. lower than crest of ridge running E. and W.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - Kody Inga - 8/1/2007 - C.S. File 67/24-2D

-----  
Found - 2 3/8" dia., brass cap on 1 1/4" O.D. iron pipe, plumb, loosely set, projects 11" above ground in duff type soil.

6" dia., spruce now tipped over on ground partly healed double blaze & tag - no position

12" dia., alder gone.

14" dia., D.Fir tipped over & slid - no position.

New - 26" dia., spruce double blazed & scribed "S 1/16 S17 CS BT" bears N.18°E., 89.1 ft.

24" dia., hemlock double blazed & scribed "S 1/16 S18 CS BT" bears S.75 1/2°W., 83.0 ft.

Note - Lies approx. 100 ft. north of rock rd, Rd is on crest of hill.

Compass decl. 16 1/4°E.