

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 2003)

-----  
Set ¼ sec. post, from which  
A Hemlock 8" dia., bears S.6°E., 22 lks. dist.  
A Hemlock 10" dia., bears West, 3 lks. dist.

Douglas County Surveyors Office - Janet Lundeen, Deputy - R. Smith and S. Flause, Crew - Sept/Dec. 1986 - C.S. 62/43-L and M 101-18

-----  
Set monument, a 2 3/8" dia. brass cap mkd:  
Douglas County Surveyors  
T 22 S  
R 12 W  
1/4 S18 | S17  
1986  
on a 1" dia., (1¼" O.D.) x 32" galv. iron pipe protruding 8" above ground and surrounded by a 2 ft. dia. mound of stone.  
New BTs -6" DBH Spruce scribed "¼ S17 CS BT" on a double blaze, bears N.75¼°E., 44.2 ft.  
16" DBH Alder bark scribed "¼ S17 CS BT" bears S.37°E., 8.4 ft.  
12" DBH Alder bark scribed "¼ S18 CS BT" bears N.79¼°W., 23.2 ft.  
10" DBH Alder bark scribed "¼ S18 CS BT" bears N.44 3/4°W., 27.5 ft.