

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 1998)

Set post corner of secs. 7, 8, 17 and 18, from which
An Alder 5" dia., bears N.23°W., 22 lks. dist.
An Alder 24" dia., bears S.58°E., 6 lks. dist.
An Alder 20" dia., bears N.35°E., 80 lks. dist.
An Alder 20" dia., bears (omitted)

Douglas County Surveyors Office - Janet Lundeen, Deputy - R. Smith and S. Flause, Crew - Sept/Dec. 1986 - C.S. 62/43-P and M 101-18

Set monument, 2 3/8" brass cap mkd: Douglas County Surveyors
Office
T 22 S
R 12 W
S 7 | S 8
S18 | S17
1986

on a 1" dia., (1 1/4" O.D.) x 32" long iron pipe protruding approx. 5" above ground.
New BTs -21" DBH Spruce scribed T22S R12W S8 CS BT on a double blaze bears N.13°E., 7.5 ft.
16" DBH Spruce scribed T22S R12W S7 CS BT on a double blazed bears N.11 1/2°W., 34.6 ft.
18" DBH Spruce scribed T22S R12W S17 CS BT on a double blaze bears S.27°E., 21.9 ft.
37" DBH Spruce scribed T22S R12W S18 CS BT on a double blaze bears S.21 1/2°W., 35.1 ft.
Monument lies on a moderate SW slope.

Fd. Ok by John Bentley, Oct. 1995 - M 123-4