

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 1999)

Set post cor. secs. 5, 6, 7 and 8, from which
An Alder 20" dia., bears S.10°E., 5 lks. dist.
An Alder 20" dia., bears N.43°E., 54 lks. dist.
An Alder 15" dia., bears N.53°W., 35 lks. dist.
A Spruce 40" dia., bears S.86°W., 53 lks. dist.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, E. West, crew - June 1967 - C.S. File 54/46-8

Found - Orig. 40" now 48" Spruce S.86°W., 35.0 ft., now badly decayed stump. Open and find "S7 T22S R12W", scribe and reverse.
No trace of other original BTs.

Set Brass cap at cor. mkd: County Surveyors Office
T 22 S R 12 W
S 6 | S 5
S 7 | S 8
1967

New BTs -20" Spruce N.46°E., 32.7 ft. mkd. T22S R12W S5 CSBT
20" Spruce S.82°E., 35.5 ft. mkd. T22S R12W S8 CSBT
11" Spruce S.40°W., 31.8 ft. mkd. T22S R12W S7 CSBT
12" Alder N.66°W., 28.7 ft. mkd. T22S R12W S6 CS BT

This corner lies in canyon bottom, course S.25°E. on E. side of ridge approx. 360 ft. from top.