

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 213100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6 only, T23-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Simon B. Cathcart, Deputy Surveyor, under Contract #559, dated Nov. 15, 1890 - (DCSO records Vol. 5 Page(s) 2066)

-----  
Set Cedar post 5" sq., 5 ft. long, 2 ft. in ground for cor. to Secs. 5 and 6 marked T23S S5 on SE.; R12W S6 on SW. faces, with 5 notches on E. and 1 notch on W. edge, from which  
A Maple 20" dia., bears S.58½°E., 95 lks. dist. mkd. T23S R12W S5 BT.  
An Alder 24" dia., bears S.45°W., 90 lks. dist. mkd. T23S R12W S6 BT.

Survey by Harvey Wilcox, LS #2244 - For: Oregon Dept. Fish and Wildlife - Dec. 1989 - M 109-52

-----  
Set a 3/4" x 30" I. Rod with 2" alum. cap, by proportion, from which  
A 23" Fir bears N.3°E., 13.2 ft. scribed "T22S R12W S32 BT" with an X at BH and tagged.  
A 28" Fir bears S.42°W., 26.4 ft. scribed "T23S R12W S6 BT" with an X at BH and tagged.  
A 24" Fir bears S.52°E., 27.2 ft. scribed "T23S R12W S5 BT" with an X at BH and tagged.

Jerry Estabrook - For: O.D.F. & W. - 8/10/2010 - M161-13 A&B

-----  
Found - A 2" aluminum cap on ¾" iron rod marked "T22S-R12W-S32-S6-S5-T23S R12W-1989-LS 2244", per CS 1B42.  
BTs - Record 23" Fir that bears N.03°E., 13.2' is now a blow down.  
A 28" fir with healed face, visible X-chop & tag bears S.52°E., 27.2'  
A 28" fir snag with face scribe & tag bears S.42°W., 26.4'.  
New BTs- A 57" maple bark scribed "NW-S5-BT" with X-chop & tag bears N.07°E., 60.1' to side center.