

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set a Spruce post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor. mkd. 1/4 S on N. face, from which  
A Spruce 48" dia., bears S.70°E., 11 lks. dist. mkd. 1/4 S BT.  
A Cedar 40" dia., bears N.77°W., 25 lks. dist. mkd. 1/4 S BT

Douglas County Surveyors Office - Janet Lundeen, Deputy - R. Smith and S. Flause, Crew - July 9, 1986 - C.S. 62/43-G and M 101-18

-----  
Found - Orig. 40" Cedar now 46" dia. Cedar snag, bears N.77°W., 16.5 ft. (rec.) We open and find scribing "1/4".  
Orig. 48" Spruce now tipped out, badly rotted stump, bears S.70°E., 7.3 ft. (Rec.)  
At record bearing and distance from Orig. 40" Cedar, SET a 2 3/8" brass cap on a 1 1/4" (I.D.) x 32" iron pipe with cap stamped: Douglas County Surveyor Office

T 22 S  
1/4 S 17  
S 20  
R 12 W  
1986

Cap protrudes 9" from ground with mound of stones around cap. New BTs -15" Spruce bears N.84 1/4°W., 16.4 ft. double blazed and scribed 1/4 S17 CS BT.  
15" Spruce bears S.19 1/2°W., 26.7 ft. double blazed and scribed 1/4 S20 CS BT.  
10" Red Cedar, pistol butted, bears S.40°E., 28.1 ft. double blazed and scribed 1/4 S20 CS BT.  
Located on South side of creek.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - Kody Inga - 8/7/2007 - C.S. File 67/24-2C

-----  
Found - 2 3/8" dia., BC, properly mkd projects 1" above ground, firmly set on steep north facing slope. 15" now 17" dia., x 2 1/2 ft. tall rotted spruce stump, F.H.D.B. bears S.19 1/2°W., 26.7 ft. (agrees w/rec) 1986 BT. FHDB= fully healed double blaze. 15" now 17" dia., x 7 ft. tall rotted & burnt spruce stump partially healed double blaze bears N.84 1/4°W., 16.4 ft. (agrees w/rec) 1986 BT. Orig. 40" now 46" x 6 ft. tall cedar stump evidence of previously opened blaze bears N.77°W., 16.5 ft. OBT. 10" R.Cedar now tipped out of position stump. 1986 BT

continued next page

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

8" boat spike mkd "BO2" driven into center of root crown of 18" dia., x 20" tall hemlock stump bears S.67½°E., 39.6 ft.  
8" boat spike mkd "BO1" driven into center of root crown of 24" dia., x 2 ft. tall D.Fir stump bears N.51¼°E., 57.0 ft.  
5/8" x 50" iron rod with 1½" dia., alum cap mkd "DOUGLAS CO SURVEYOR BO 3 2007" projects 18" above ground, bears N.43½°W., 21.9 ft.  
Note - Lies on very steep north facing slope on south side of seasonal drainage, in area of newly planted trees.  
Compass decl. 16¼°E.