

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCS0 records Vol. 5 Page(s) 2000)

Set ¼ sec. post, from which
A Spruce 30" dia., bears S.74½°E., 20 lks. dist.
A Spruce 10" dia., bears N.4½°W., 34 lks. dist.

Survey by Richard Hintz - For: Douglas County Land Dept. - May 1983 - C.S. File 58/140 and M 94-34

Set 1¼" x 36" I.P. with stamped brass cap "PLS 497"
New BTs -18" Spruce bears N.51°30'E., 11.8 ft. scribed.
22" Fir bears S.21°00'E., 24.1 ft. scribed.

Fd. OK, Jan. 23, 1989 by Les Roberts - C.S. File 63/46-7(G)
Fd. Ok by John Bentley, Oct. 1995 - M 123-4

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 9/4/2025 - C.S. File 67/61-21

Found - 2½" Brass cap on iron pipe proj. 2".
Very rotted 22"x3 ft spruce stump. N.51°30'E.
11.8 ft. Rotted blaze - scar.
Very rotted 18"x4½ ft fir stump. S.21°E. 24.1 ft.
Blaze mostly rotted, partial scribes S8 B7 visible. Spike nail left side center.

PLS 497

1 S5
4 S8

1983

T25S R12W

New - 4" Hemlock N.65°E. 8.6 ft scribed "X BT" on double blaze.
12" D. Fir S.20°E. 3.5 ft scribed "¼ S8 BT" on double blaze
10" D. Fir S.74°W. 7.5 ft scribed "¼ S8 BT" on double blaze
11" D. Fir N.17½°W. 10.3 ft scribed "¼ S8 BT" on double blaze.

Notes - Mon in older reprod near top of moderate east slope. Approx 150 ft N.N.E. of short logging spur.

Compass decl. 14½°E.
OCSRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
43°40'57.35866" N.
124°09'15.45486" W.