

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 252100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 5 only, T23-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #341, dated October 4, 1879 (DCSO records Vol. 5 Page(s) 2022)

-----  
Set Cedar post 4x4 by 5 ft. long in ground for ¼ sec. corner, from which

A Fir 30" dia., bears N.43°W., 23 lks. dist.

A Cedar 24" dia., bears S.76°E., 13 lks. dist.

-----  
Survey by Harvey Wilcox - For: Oregon Dept. of Fish and Wildlife - Dec. 1986 - M 103-31

-----  
Corner report only.

Found 3/4" Iron rod with 2" alum. cap at orig. corner position as perpetuated by R.E. Stuntzner in July 1982, recorded in Coos County records, M 1B27, from which

Orig. 30" D.Fir, remains only, N.43°W., 15.2 ft.

Orig. 24" Cedar windfall, S.76°E., 8.6 ft.

1982 BT, 22" D.Fir S.79°E., 38.3 ft. visible scribe.

1982 BT, 20" D.Fir S.14°W., 41.8 ft. visible scribe.

-----  
Fd. OK, July 1990 - M 112-9