

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2052)

-----  
Set a Fir post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which  
A Fir 27" dia., bears N.51°W., 15 lks. dist. mkd. ¼ S BT  
A Hemlock 36" dia., bears S.85°E., 17 lks. dist. mkd. ¼ S BT.

John Minor, L.S. #2052 - For: Menasha Corp., Moore Mill, & Douglas County -November 1994 - M 121-32

-----  
Found - Scribing on original BT S.85°E., 11.22 ft. to face.  
Set 2"x 30" I.P. with 2" brass cap 12" above ground mkd: T22S R12W, 1/4, S20 S21, 1994, LS 2052., from which  
14" Cedar, N.52.5°E., 25.9 ft., scribed ¼ S21 BT.  
Hemlock snag, S.85°E., 11.9 ft., to face (Orig. scribing vis.)  
33" Hemlock, S.52.5°E., 40.7 ft., scribed ¼ S21 BT.  
28" Cedar, S.3.75°W., 49.8 ft., scribed ¼ S20 BT.  
23" Alder, S.82.5°W., 46.3 ft., bark scribed ¼ S20 BT.