

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 2002)

Set ¼ sec. post, from which
 An Alder 18" dia., bears S.63°E., 40 lks. dist.
 A Spruce 15" dia., bears N.10°W., 39 lks. dist.

Survey by Richard Hintz - For: Douglas County Land Dept. - May 1983 - C.S. File 58/140 and M 94-34

Set 1¼" x 36" I.P. with stamped brass cap "PLS 497"
New BTs -30" Fir bears S.48°00'E., 10.4 ft., scribed.
 20" Fir bears S.30°30'W., 10.1 ft., scribed.

John Bentley, L.S. 2656 - For: Menasha Corp. - Oct. 1995 - M 123-4

Found - 2" I.P. with B.C. (M94-34)
 33" D.Fir, S.48°E., 10.4', healed face.
 23" D.Fir, S.30°30'W., 10.1', healed face.
New BTs- 21" D.Fir, N.58°E., 10.6', scribed ¼ S9 BT.
 22" Hemlock, N.64°W., 25.2', scribed ¼ S8 BT.