

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 2001)

Set ¼ sec. post, from which
A Spruce 15" dia., bears S.43°W., 38 lks. dist.
A Fir 36" dia., bears S.40°E., 25 lks. dist.

Survey by Robert Thompson - For: Edin Properties - April/Nov. 1973 - C.S. File 55/328 and M 51-65

Found - Old squared 5"x5"x36" Post, down, not in true position.
OBT, 24" rotted Spruce stump with old axe work, S.43°W., 25.0 ft.
OBT 48" D.Fir stump with old face scribe destroyed by logging, S.40°E., 16.5 ft.
Set 1¼" I.P.
Scribe "¼S 3683 BT" on:
19" Hemlock S.81°30'E., 17.6 ft.
9" Hemlock S.44°W., 12.5 ft.

Fd. OK, Feb. 18, 1975, by DCSO, L.E.M. - C.S. File 59/46-68
Fd. OK, March 1987 by R. Hintz - M 103-59

Fd. OK, Jan. 20, 1989 by Les Roberts - C.S. File 63/46-7(D) (who set 60" alum. post, with land survey monument sign attached to, beside 1¼" I.P. Painted all BTs red.)

Fd. OK, Sept. 1993 - M 117-64