

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5 only, T23-12

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #341, dated October 4, 1879 (DCSO records Vol. 5 Page(s) 2021-22)

-----  
Set Hemlock post 4x4 by 5 ft. long in ground for corner to secs. 4, 5, 32 and 33, from which  
An Alder 10" dia., bears N.14°W., 12 lks. dist.  
A Hemlock 6" dia., bears S.24°W., 10 lks. dist.  
A Hemlock 7" dia., bears S.45°E., 8 lks. dist.  
An Alder 12" dia., bears N.17°W., 35 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2057-58)

-----  
Cor. to Secs. 4 and 5, which is a Hemlock post 4" sq., 24" in the ground, marked S33 T22S on NE. face; S4 R12W on SE. face; S5 T23S on SW. face; S32 on NW. face, from which  
An Alder 10" dia., bears N.14°E., 12 lks. dist. mkd. S33 T22S R12W BT.  
A Hemlock 7" dia., bears S.45°E., 8 lks. dist. mkd. S4 T23S R12W BT.  
A Hemlock 6" dia., bears S.24°W., 10 lks. dist. mkd. S5 T23S R12W BT.  
An Alder 12" dia., bears N.17°W., 35 lks. dist. mkd. S32 T22S R12W BT.  
I destroyed marks referring to Sec. 32 on post and bearing trees.

Survey by D.L. Buckingham (his field book 9) - For: Buchner survey - May 1919 - DCSO records, C.S. File 62/35 Page 56

-----  
NW cor. Sec. 4. Iron pipe, 2 old posts and witness tree.

Survey by Warren D. Hootman - Oct. 27, 1959 - C.S. File 51/55

-----  
Set by single proportion.  
Set a 3" post and mark the following bearing trees:  
9" D.Fir bears S.81°00'E., 14.8 ft.  
6" D.Fir bears S.26°00'W., 11.1 ft.  
8" D.Fir bears N.65°00'W., 2.0 ft.  
16" Alder bears N.18°15'E., 14.0 ft.

(Cont. Next Page)

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 317100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5 only, T23-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ronald Stuntzner - Dec. 10, 1986 - M 103-31

-----

Section corner per propoition:

- 1" Iron pipe.
- 20" D.Fir N.40°E., 23.4 ft.
- 24" D.Fir S.70°W., 18.5 ft.
- 10" D.Fir S.50°E., 14.8 ft.