

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2055)

Set a Cedar post 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor., from which

An Alder 15" dia., bears S.78 1/2°W., 152 lks. dist. mkd. 1/4 S BT.

An Alder 16" dia., bears N.16°W., 120 lks. dist. mkd. 1/4 S BT.

Douglas County Surveyors Office - L.E. Monrean, Deputy - P.L. Earle; S.J. Flause, crew - Nov. 28, 1978 - C.S. File 60/17-28

Found - Scribed stone recorded by Hootman (marking appears to be a portion of a 4) set flush with ground. Stone located by measuring from monuments recorded on Map M 22-28. (See also C.S. File 51/61) (No record of who set scribed stone found)
Orig. BTs and orig. monument not found.

New Accessories:

D.Fir 7", double blazed and scribed "1/4 S28 CS BT" bears N.44°W., 179.4 ft.

Alder 15", bark scribed "1/4 S33 CS BT" bears S.68°W., 207.0 ft.

Set a bridge spike midway on most southerly rail (curb) of bridge over Scholfield Creek. Spike is marked "B.O. 1" and bears N.2 1/2°E., 123.7 ft.

A County Surveyors brass cap set in concrete tile marked "SC 14 1975" bears N.86°E., 100.9 ft.

Fd. OK, May 1994 by J. Minor - M 120-10

Douglas Co. Surveyors Office - Randall Smith & Stephen Flause - 4/20/1995 - C.S. File 64/63-8

Found - Large roundish sand stone flush with ground. Top is approx. 18" dia, with illegible marks. (source unknown)

5/8" I.R. protruding 1" above ground, bears S.45°W., 1' from center of stone (source unknown)

Accessories Fd - Brg & dist taken to center of stone monument
7" now 12" dia., D.Fir, with a fully healed double blaze, bears N.44.W., 180'.

15" now 23" dia., Alder, with illegible bark scribing, we re-bark scribe "1/4 S33 CS BT", bears S.68°W., 207'.

Continued next page

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Boat spike in bridge marked "B01", bears N.2½°E.,
123.7', bridge will be changed and BS will be
lost in near future.
DCSO brass in concrete monument marked "SC 14 1975",
bears N.87°E., 101.5'.
New - 24" dia., Spruce, double blazed and scribed "¼ S28
CS BT", bears N.27°W., 165'.
Corner lies approx 2' easterly of a northerly-southerly fence
line