

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 354100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 4 only, T23-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #341, dated October 4, 1879 (DCSO records Vol. 5 Page(s) 2021)

Set Cedar post, 4x4 by 4 ft. long in ground for ¼ sec. corner, from which

A Maple 12" dia., bears N.22°E., 23 lks. dist.

A Cedar 30" dia., bears N.24°W., 23 lks. dist.

Survey by Warren D. Hootman - 1959 - C.S. File 51/55 and C.S. 58/37

I make a search for the ¼ corner but cannot verify any evidence of the original corner.

Set 4" Post and mark the following bearing trees:

48" Cedar bears N.85°00'W., 18.5 ft.

38" Cedar bears S.83°30'W., 43.8 ft.

Survey by Ronald Stuntzner - Dec. 10, 1986 - M 103-31

Set 5/8" x 30" Iron rod with I.D. cap mkd. Stuntzner Eng., from which

58" Western Red Cedar bears S.84°W., 16.9 ft.