

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2045-46)

For closing cor. to secs. 33 and 34, I set a Cherry post, 4 ft. long, 4" sq., 24" in the ground marked C C T22S R12W on N.; S34 on E.; S33 on W. faces with 3 notches on E. and W. faces, from which

A Cherry 5" dia., bears S.54½°E., 18 lks. dist. mkd. T23S R12W S4 BT.

A Cherry 12" dia., bears N.88½°E., 19 lks. dist. mkd. T22S R12W S34 BT.

A Cherry 4" dia., bears N.67°W., 18 lks. dist. mkd. T22S R12W S33 BT.

Survey by Thomas J. Hoesly - For: Menash Corp. - Dec. 20, 1978 - M 74-64

Set a 2" x 36" galv. I.P., from which

A 20" Cherry bears N.33°E., 18.4 ft., scribed.

A 70" Hemlock bears S.53°E., 75.4 ft., scribed.

A 34" Hemlock bears S.79°30'W., 38.0 ft., scribed.

A 4" Hemlock bears N.49°30'W., 25.3 ft., blazed.

Douglas Co. Surveyors Office - Greg Quibell, Deputy - T. Plouff, Wit - Feb. 23, 1982 - C.S. File 61/30-15

Found - 2" x 36" galv. I.P. firmly set, protruding 8" out of ground.

20" Cherry, now dead, with scribed "BT S T" visible in partially burned unhealed face, bears N.33°E., 19.2 ft. (Rec. 18.4 ft.)

70" Hemlock now 48" stump with scribed "BT S4 T23 R12" visible in unhealed face bears S.53°E., 78.3 ft. (Rec. 75.4 ft.)

34" Hemlock now 65" stump with scribed "S33 T22 R12" visible in unhealed face, bears S.79°30'W., 40.6 ft. (Rec. 38.0 ft.)

(Record distances were possibly taken to face of tree instead of center)

After referencing found I.P., I SET a 1" x 36" I.P. with brass cap attached in its place. Cap is mkd. "Douglas Co. Surveyor T22S S33 S34 R12W S4 T23S 1982". The found 2" I.P. was buried along North edge of brass cap. A green metal fence post was also placed just North of corner.

New Accessories:

(Cont. Next Page)

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Boat Spike stamped "BO 1" in face of 20" Cherry BT,
bears N.33°E., 18.8 ft.
Boat Spike stamped "BO 2" in top of 72" Hemlock
stump, bears N.69°E., 143.9 ft.
Boat Spike stamped "BO 3" in face of 48" Hemlock
stump BT, bears S.53°30'E., 75.6 ft.
Boat Spike stamped "BO 4" in top of 36" Hemlock
stump bears S.37½°W., 87.9 ft.
Boat Spike stamped "BO 5" in top of 65" Hemlock
stump, bears S.81°W., 39.4 ft.
Metal fence post with survey marker sign and line crossing
tag bears South 25.2 ft. BT tags on all stumps.
Corner lies in new clearcut.