

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2042)

Set a Spruce post 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S. on W. face, from which

An Alder 24" dia., bears N.58 1/2°E., 27 lks. dist. mkd. 1/4 S BT.

An Elder 6" dia., bears N.60 1/2°W., 8 lks. dist. mkd. 1/4 S BT.

Survey by Warren D. Hootman - For: Cape Arago Lumber Co. - Nov. 20, 1959 - C.S. File 51/61 and M 16-51

Set cor. at the proportioned distance and on the true line by:

Driving a 1 1/2" Pipe, from which

16" Alder DBH, bears N.42°00'W., 13.3 ft.

22" Alder DBH, bears N.85°00'E., 20.2 ft.

Fd. OK, April 17, 1973 - C.S. File 56/25

Douglas Co. Surveyors Office - Karen Reed; Terrie Plouff, crew - April 2, 1980 - C.S. File 61/6-26

Found - 1 1/2" Iron pipe protruding 2.1 ft. above ground. Pipe measures 5 ft. in length.

No orig. trees found.

A 16" Alder now an 18" with partially healed blaze, no scribing on face, bears N.42°W., 13.3 ft.

A 22" Alder now an 18" with partially healed blaze with visible scribe "1/4 S", bears N.85°E., 20.2 ft.

Set 1" x 36" Iron pipe with brass cap stamped "Douglas County Surveyor T22S R12W 1/4 S28 S27 1980" at position of pipe. Set pipe on East side of cap, protruding 2.4 ft. above ground.

New BTs -An 18" Alder scribed "1/4 S27 CS BT" in a double blaze bears S.71°E., 45.6 ft.

A 15" Alder scribed "1/4 S28 CS BT" in a double blaze bears S.70°W., 17.3 ft.

Located on slope descending North approx. 330 ft. southerly of RR tracks.