

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2039-40)

A Cedar 10" dia., which I mark $\frac{1}{4}$ S on W. face for $\frac{1}{4}$ sec. cor., from which

A Cedar 18" dia., bears N.11°E., 34 lks. dist. mkd. $\frac{1}{4}$ S BT

A Fir 30" dia., bears S.11°W., 32 lks. dist. mkd. $\frac{1}{4}$ S BT.

Fd. Cedar post and Fir BT, June 1916 by A.N. Gould Field Book 53 Page 123 (DCSO records, C.S. File 62/35)

Survey by Robert B. Ward, Jr. - For: Champion International Corp. - Nov. 1981/June 1982 - M 92-58

Found no trace of 1889 GLO corner or accessories.

At point of proportionate measure, SET a 2½" brass cap on 2½" x 30" I.P. with stamped LS 1091.

New BTs -13" Fir bears N.72°00'W., 14.5 ft. scribed $\frac{1}{4}$ S21 BT.

13" Fir bears S.13°00'E., 8.3 ft. scribed $\frac{1}{4}$ S22 BT.

Fd. OK, Nov. 1994 by J. Minor - M 121-32