

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2037)

-----  
Set a Cedar post 4 ft. long, 6" sq., 24" in the ground, for cor. to secs. 15, 16, 21 and 22, mkd. T22S S15 on NE.; R12W S22 on SE.; S21 on SW.; S16 on NW. faces, with 3 notches on S. and E. edges, from which

A Cedar 8" dia., bears N.1 3/4°E., 31 lks. dist. mkd. T22S R12W S15 BT.

A Cedar 10" dia., bears S.18½°E., 24 lks. dist. mkd. T22S R12W S22 BT.

A Cedar 10" dia., bears S.15½°W., 18 lks. dist. mkd. T22S R12W S21 BT.

A Cedar 30" dia., bears N.56½°W., 11 lks. dist. mkd. T22S R12W S16 BT.

Survey by Robert B. Ward, Jr. - For: Champion International  
Nov. 1981/June 1982 - M 92-58

-----  
Found - 35" Cedar stump with scribing visible on reverse at face. bears N.44°30'W., 7.3 ft. (1889 BT)

26" Cedar in position for the SE BT, bears S.20°00'E., 15.8 ft. (1889 BT)

NE and SW BTs are missing.

At the point of intersection of the record distance, SET a 2½" brass cap on 2½" x 30" I.P. mkd. LS 1091.

New BTs -16" Fir bears N.76°00'E., 13.9 ft. scribed T22S R12W S15 BT.

12" Fir bears S.32°00'W., 5.2 ft. scribed T22S R12W S21 BT.

Fd. OK, March 992 by H. Wilcox - M 115-4