

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/5 Cor. for Secs. 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2036-37)

Set a Spruce post 4 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Fir 42" dia., bears S.55°W., 8 lks. dist. mkd. ¼ S BT.
A Fir 40" dia., bears S.87°E., 49 lks. dist. mkd. ¼ S BT.

Survey by Robert B. Ward, Jr. - For: Champion International - Nov.1981/June 1982 - M 92-57

Found no trace of 1889 GLO corner or accessories.
At point of proportionate measure, SET a 2½" brass cap on a 2½" x 30" I.P. stamped with LS #1091.
New BTs -10" Fir bears N.20°00'E., 10.9 ft. scribed ¼ S15 BT
11" Hemlock bears S.46°00'W., 7.3 ft. scribed ¼S16 BT.

Cor. Fd. OK, July 15, 1987 by Les Roberts - C.S. File 63/55-2 and M 105-30. Roberts set 60" alum. post with land survey sign attached to, beside brass cap. Painted all BTs red.

Survey by Harvey Wilcox - For: I.P. Timberlands - March 1992 - M 115-4

Found - 2½" brass cap on 2" ODIP (Ward) stamped with LS #1091 with alum. post alongside.
12" Fir with healed face and tags, bears N.20°E., 10.9 ft.
18" Hemlock with visible scribe and tags, bears S.46°W., 7.3 ft.
New BTs -8" Fir, face scribed, "¼ S16 BT" with "X" and tags, bears N.51°W., 3.1 ft.
10" Fir face scribed, "¼ S15 BT" with "X" and tags, bears S.60°E., 27.8 ft.