

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2033)

Set an Alderwood post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 9, 10, 15 and 16, mkd. T22S S10 on NE.; R12W S15 on SE.; S16 on SW.; S9 on NW. faces, with 4 notches on S. and 3 notches on E. edges, from which

A Spruce 36" dia., bears N.48½°E., 72 lks. dist. mkd. T22S R12W S10 BT.

A Spruce 36" dia., bears S.84°E., 61 lks. dist. mkd. T22S R12W S15 BT.

A Spruce 30" dia., bears S.½°W., 81 lks. dist. mkd. T22S R12W S16 BT.

A Fir 30" dia., bears N.69½°W., 109 lks. dist. mkd. T22S R12W S9 BT.

Survey by Robert B. Ward, Jr. - For: Champion International Corp. - Nov. 1981/June 1982 - M 92-57

Found - 36" Spruce stump with scribing visible (SW BT), bears S.7°30'W., 56.4 ft. (1889 BT)

Rotted Spruce stump bears N.46°00'E., 49.4 ft. (1889 BT)

Rotted Spruce stump bears S.82°30'E., 40.5 ft. (1889 BT)

At the point of intersection of the record distances, SET a 2½" brass cap on a 2½" x 30" I.P. with LS #1091 stamped.

New BTs -12" Alder bears N.48°00'E., 38.9 ft. barks scribed T22S R12W S10 BT.

12" Hemlock bears S.22°00'E., 17.1 ft. scribed T22S R12W S15 BT.

14" Hemlock bears S.44°00'W., 55.0 ft. scribed T22S R12W S16 BT.

16" Alder bears N.30°00'W., 37.9 ft. bark scribed, T22S R12W S9 BT.

Cor. Fd. OK, July 10, 1987 by Les Roberts - C.S. File 63/55-1 and M 105-30. Roberts set 60" alum. post with land survey monument sign attached to, beside brass cap. Painted all BTs red.