

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2032)

Set a Vine Maple post 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., mkd. ¼ S on W. face, from which

A Vine Maple 6" dia., bears East, 10 lks. dist. mkd. ¼ S BT.

A Vine Maple 4" dia., bears West, 4 lks. dist. mkd. ¼ S BT

Survey by Bruce A. Shaner - For: Moore Mill & Lumber Co. - June 1982 - RM 3-59

Set Brass cp mkd. T22S R12W WM 1/4 S9 S10 Shaner Engineering RLS 430 1982, from which a:

18" D.Fir, I scribed "¼ S10 BT", bears S.80°E., 84.3 ft.

28" Hemlock, I scribed "¼ S9 BT", on bark, bears S.46°W., 75.0 ft.

Corner falls in bottom of a draw, North 120 ft. from the top of a main ridge, which runs E-W.

Fd. BC & 2 BTs 4/9/1987 by Les Roberts C.S. File 63/55-5 - Set 60" alum. post with land survey monument sign attached to, beside brass cap. Painted all BTs red.