

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 3, 4, 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 1997)

Set post Cor. of Secs. 3, 4, 9 and 10, from which
A Cedar 12" dia., bears N.12°W., 18 lks. dist.
A Fir 30" dia., bears S.18½°W., 27 lks. dist.
A Spruce 18" dia., bears N.85°E., 44 lks. dist.
A Cedar 12" dia., bears S.10°E., 28 lks. dist.

Cor. Fd. and used in GLO survey by Wm. Thiel, Deputy Surveyor under Contract #534, dated Jan. 1889 - (DCSO records, Vol. 5 Pages 2031-32)

Douglas County Surveyors Office - James Byron, Deputy - For: Warren Waggoner - Aug. 9, 1956 - C.S. File 47/129

Found - Orig. 12", now 30" Cedar N.12°W., record bearing and dist. Alive but partly rotted. We open and find scribe marks.

Orig. 18" now 30" Spruce N.85°E., 29 ft. Tree in good condition and we do not open, shows good blaze.

Both original BTs check for bearing and distance.

Set an Iron pipe with brass cap at corner point mkd. "4 3
T22S R12W, 1956" 9 10

Blazed and scribed:

10" Hemlock N.40°W., 19.6 ft. mkd. T22S R12W S4 CS
BT.

12" Hemlock S.71°W., 25.0 ft. mkd. T22S R12W S9 CS
BT.

12" Cedar N.12°W., mkd. S4 CS BT. (Orig. BT)

No trees in SE. quad.

Fd. OK, June 1982 by B. Shaner - RM 3-59

Fd. OK, Sept. 1993 - M 117-64