

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2041)

A Cedar 36" dia. which I mark $\frac{1}{4}$ S. on N. face, from which
A Fir 40" dia., bears N.70°E., 14 lks. dist. mkd. $\frac{1}{4}$ S BT.
A Fir 30" dia., bears S.80°W., 13 lks. dist. mkd. $\frac{1}{4}$ S BT.

Fd. OK, by A.N. Gould - 1916 - Gould Field Book 53 Page 101 (DCSO records, C.S. File 62/35)

Survey by Warren D. Hootman - For: Cape Arago Lumber Co. of Empire, Ore. - Nov. 20, 1959 - C.S. File 51/61 and M 16-51

Found - I find the Cedar corner tree with the face burned out.
The BT for Sec. 27 is down with the face buried.
The BT in Sec. 22 is a stump with the face healed over.

I mark new bearing trees as follows:
D.Fir 18" DBH, bears S.22°00'E., 18.0 ft.
D.Fir 16" DBH, bears S.80°00'W., 14.5 ft.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, L. Monrean; G. Commons - April 19, 1973 - C.S. File 56/25-11

Found - 18" D.Fir now 22", S.22°E., 18.0 ft. shows good scar
16" D.Fir now 19" S.80°W., 14.5 ft. shows good scar.
Also Cedar corner tree, now snag.

Set Brass cap on East side of cor. tree mkd:
County Surveyors Office
T 22 S R 12 W

$\frac{1}{4}$ $\frac{S\ 22}{S\ 27}$
1973

New BT - 14" Hemlock N.52°E., 26.2 ft. scribed $\frac{1}{4}$ S22 CS BT.

Survey by Robert W. Ward, Jr. - For: Champion International -Nov. 1981/June 1982 - M 92-58

Found 38" Cedar snag with chopped face on North side with the following accessories:

42" Fir stump with scribing visible bears N.74°00'E., 10.4 ft. (1889 BT)

Rotted Fir stump bears S.80°00'W., 8.5 ft. (1889 BT)

Set a 2½" brass cap on a 2½" x 30" I.P. with stamped LS #1091

New BTs -15" Fir bears N.87°30'E., 20.2 ft. scribed X BT.

60" Fir bears N.0°30'E., 43.3 ft. scribed X BT.

(Cont. Next Page)

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Corner tree bears N.89°12'06"W., 21.04 ft.
Note: Corner as called by PLS 399 and Douglas Co. Surveyors Office bears S.4°17'44"W., 359.34 ft.

Douglas Co. Surveyors Office - Karen Reed and John Powell, crew - Aug. 16, 1982 - C.S. File 62/1-7

Found - 1½" Iron pipe with 1973 county brass cap on East side of Cedar snag.

I cut off brass cap and set yellow plastic cap in pipe mkd. "Doug. Co. Surveyor" as a result of original corner evidence found and recorded by R. Ward and filed as M 92-58.

Found - an 18" dia., D.Fir now 28" with well healed double blaze, bears S.22°E., 18.0 ft. I open and deface scribe "¼ S27"

A 16" D.Fir now 20" with well healed double blaze bears S.80°W., 14.5 ft. I open and deface scribe "¼ S27 BT"

A 14" hemlock with partially healed double blaze bears N.52°E., 26.2 ft. I deface visible scribe "¼ S22".

New corner position determined by Robert Ward.