

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2039)

On divide, set a Fir post 3 ft. long, 5" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which
A Fir 30" dia., bears N.19½°W., 13 lks. dist. mkd. ¼ S BT
A Fir 36" dia., bears S.80½°W., 12 lks. dist. mkd. ¼ S BT

Survey by Robert B. Ward, Jr. - For: Champion International -Nov. 1981/June 1098 - M 92-58

Found both Fir BTs with scribing visible:
32" Fir stump bears N.8°00'W., 8.6 ft. (1889 BT)
40" Fir stump bears S.83°00'W., 7.9 ft. (1889 BT)
Set 2½" brass cap on 2½" x 30" I.P. with stamped LS 1091.
New BTs:
14" Spruce bears N.62°00'W., 21.1 ft. scribed ¼ S15 BT.
11" Spruce bears S.65°00'W., 32.2 ft. scribed ¼ S22 BT.