

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2034)

Set a Vine Maple post, 3 ft. long, 3" sq., 24" in the ground, mkd. ¼ S on N. face, from which

An Alder 16" dia., bears N.67½°W., 37 lks. dist. mkd. ¼ S BT.

A Spruce 30" dia., bears S.3½°W., 30 lks. dist. mkd. ¼ S BT.

Survey by A. N. Gould - 1916 - Gould Field Book 53 Page 145 (DCSO Records, C.S. File 62/35)

Set new Cedar post ¼ S bet 10 & 15.

Found Spruce 30" S.3½°W., 30 lks.

Alder N.67½°W., 37 lks. fallen.

Marked Alder 24" N.84½°E., 28.7 ft.

Survey by Robert B. Ward, Jr. - For: Champion International -Nov. 1981/June 1982 - M 92-57

Found no trace of 1889 GLO corner or accessories.

At point of proportionate measure, SET a 2½" brass cap on a 2½" x 30" I.P. with LS #1091 stamped., from which

12" Alder bears S.16°00'W., 5.5 ft. barks scribed, ¼ S15 BT.

10" Alder bears N.68°00'W., 11.2 ft. bark scribed, ¼ S10 BT.

Fd. BC & 2 BTs 7/15/1987 by Les Roberts C.S. File 63/55-11 - Painted all BTs red.