

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 1998)

-----  
Set ¼ sec. post, from which  
A Cedar 36" dia., bears S.22°E., 27 lks. dist.  
A Hemlock 12" dia., bears N.65°E., 40 lks. dist.

-----  
Douglas County Surveyors Office - James W. Byron, deputy -  
For: Warren Waggoner - Aug. 9, 1956 - C.S. File 47/129

-----  
Corner could not be found after thorough search. Position of cor. established on true line at mid point between section corners.  
Set an iron pipe with brass cap mkd: "¼ S3 10 T22S R12W County Surveyors Office 1956".  
Blazed and scribed:  
5 ft. Spruce S.66°E., 13.71 ft. mkd. ¼ S10 CS BT.  
20" Cedar S.16°E., 19.24 ft. mkd. ¼ S10 CS BT.

-----  
Fd. OK, June 1982 by B. Shaner - RM 3-59