

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 452100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 3 only, T23-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #341, dated October 4, 1879 (DCSO records Vol. 5 Page(s) 2020)

Set Alder post 5x5 by 5 ft. long, in ground for ¼ sec. corner, from which
 An Alder 12" dia., bears N.9°W., 17 lks. dist.
 An Alder 12" dia., bears S.72°W., 29 lks. dist.

Cor. Fd. and used in GLO survey by Wm. Thiel, 1889 (DCSO records, Vol. 5 Page 2046)

Survey by Ronald E. Stuntzner - Nov. 14, 1970 - C.S. File 55/172

Set ¼ corner at proportionate distance, 2,717.66 ft.
Set 1' iron pipe, from which
 8" Chittum S.82°E., 2.4 ft.
 18" Fir S.14°W., 60.2 ft.
 24" Fir S.23½°E., 64.3 ft.

Survey by Lloyd D. Smith, LS #1101 - For: Oregon State Board of Forestry - Dec. 1985 - M 100-37

Found 1" galv. I.P. (1970 Stuntzner), now bears S.06°W., 13.5 ft. from new corner position, from which
 4"x4"x72" white painted cedar post bears N.33°W., 2.0 ft.
 22" Fir bears S.12°W., 72.6 ft. with a BT tag. (Stuntzner BT)
 29" Fir bears S.20°E., 76.4 ft. (Stuntzner BT)
 11" Chittum bears S.03°E., 13.8 ft. to North side. (Stuntzner BT)
Set an OSDF 1½" x 36" alum. pipe with a 3 3/4" dia. alum. cap with magnetic insert, at corner position, 34" in ground, from which new BT,
 22" Alder bears S.50°E., 35.6 ft. Bark scribed "¼ S3 BT" with a BT tag in place.