

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION C C for Secs. 34 and 35 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2031)

For closing cor. to secs. 35 and 34, I set a Myrtle post, 4 ft. long, 4" sq. 24" in the ground, marked CC T22S R12W on N.; S35 on E.; and S34 on W. faces, with 2 notches on E. and 4 notches on W. faces, from which

A Myrtle 8" dia., bears N.42°E., 8 lks. dist. mkd. T22S R12W S35 BT.

An Alder 6" dia., bears N.16°W., 36 lks. dist. mkd. T22S R12W S34 BT.

A Fir 36" dia., bears S.36½°E., 55 lks. dist. mkd. T23S R12W S3 BT.

Survey by Lloyd D. Smith, LS #1101 - For: Oregon State Board of Forestry - Dec. 1985 - M 100-37 (Fd. and used in Jan. 1986, M 100-38)

Set OSDF 1½" x 36" alum. pipe with a 4/5" dia. alum. cap and magnetic insert. Pipe is 34" in ground, from which

19" Fir bears N.50°E., 20.3 ft. scribed "T22S R12W S35 CC BT" with a BT tag, in place.

22" Fir bears N.10°W., 2.3 ft. scribed "T22S R12W S34 CC BT" with a BT tag, in place.

Set a 4"x4"x72" white painted cedar post bearing N.74°E., 1.8 ft. dist.