

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #323, dated May 26, 1879, - (DCSO records Vol. 5 Page(s) 2017-18)

Set a Fir post 40" long, 20" in ground, for the corner to sections 22, 23, 26 and 27, from which

- A Cedar 20" dia., bears N.37°E., 46 lks. dist.
- A Cedar 10" dia., bears S.89°W., 117 lks. dist.
- A Cedar 10" dia., bears S.20°W., 100 lks. dist.
- A Cedar 20" dia., bears N.50°W., 95 lks. dist.

Fd. and used in GLO survey by Wm. Thiel under Contract #534, dated Jan. 12, 1889 (DCSO records, Vol. 5 Pages 2026-27)

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Lloyd D. Smith, transitman - July 16, 1969 - C.S. File 55/101-10 & 16

Original Fir post, missing, from which a:

- 20" Cedar bears N.37°E., 46 lks.; now 65" in place, face has been partially opened, no scribes visible.
- 10" Cedar bears S.89°E., 117 lks.; missing.
- 10" Cedar bears S.20°W., 100 lks.; now 32" windfall, face open, scribes 27 visible.
- 20" Cedar bears N.50°W., 95 lks.; missing.

Set 1½" x 36" galv. Iron pipe with 3" bronze cap mkd. "Ore. St. Bd. of Forestry T22S R12W S22 S23 S26 S27 1969 RS 359", 34" in ground and from which a:

- 65" Cedar, orig., bears N.37°E., 30.4 ft. scribed RS 359.
- 17" Alder bears N.40°W., 70.0 ft. scribed T22S R12W S22 BT
- 16" Alder bears S.13°E., 32.2 ft. scribed T22S R12W S26 BT
- 8' x 15' sandstone face bears S.20½°W., 31.5 ft. to 8 in. "X", scribed X BO.

Set 4x4x72" white painted cedar post 2.4 ft. N.60°E. of corner pipe.

OSFD metal location poster on orig. Cedar N.37°E., 30.4 ft

Fd. OK, June 1987 by M. Hoyer - M 104-31