

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #323, dated May 26, 1879, - (DCSO records Vol. 5 Page(s) 2017)

Marked an Elder 5" dia. for the quarter section corner between secs. 22 and 23, from which
A Maple 10" dia., bears S.15°E., 30 lks. dist.
An Alder 16" dia., bears N.25°W., 68 lks. dist.

Survey by Robert B. Ward Jr. - For: Champion International Corp. - Nov. 1981/June 1982 - M 92-58

Found no trace of 1879 GLO corner or accessories.
At point of proportionate measure, SET a 2½" brass cap on a 2½" x 30" I.P. with stamped LS #1091.
New BTs -22" Alder bears S.75°30'W., 9.9 ft. bark scribed ¼ S22 BT.
21" Alder bears N.12°00'E., 42.4 ft. bark scribed ¼ S23 BT.

Survey by Bruce Shaner - For: Moore Mill & Lumber Co. - Feb. 1987 - RM 3-66 A&B

Found a 2½" brass cap with a 2" iron pipe mkd. ¼ S22 S23 1982 from which
A 22" Alder BT bears S.75½°W., 9.9 ft.
21" Alder BT bears N.12°E., 42.4 ft.
This corner was set in the wrong place by Surveyor Ward, per this survey.

Set a 2½" brass cap on a 2" x 34" Iron pipe mkd. "¼ S22 S23 1987 RLS 430"., from which
An 18" Spruce bears N.48°E., 13.4 ft. scribed ¼ S23 BT.
24" Hemlock stump bears N.40°W., 2.5 ft. scribed ¼ S22 BT
Sec. 22 has been recently clearcut logged.

Fd. OK, May 1991 - M 113-35 A&B