

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 5 Page(s) 2014)

-----  
Set a Fir post for ¼ sec. cor., from which  
A Fir 40" dia., bears N.12°E., 32 lks. dist.  
A Spruce 16" dia., bears S.47°W., 25 lks. dist.

Survey by Richard Hintz - For: Champion International - Oct. 1978 - M 74-4

-----  
Set a stamped 2" I.P. with brass cap, from which  
40" Fir stump bears N.12°E., 21.1 ft. (orig. BT)  
48" Spruce bears S.47°W., 16.5 ft. (orig. BT)  
56" Spruce bears S.7°E., 21.7 ft., scribed. (New BT)  
20" Hemlock bears N.52°W., 27.3 ft., scribed. (New BT)

Tony Hostetter - For: Rayonier - Jan. 2017 - M173-17

-----  
Found - 1978 brass cap as set by Hintz (M74-4). And BTs (all stumps) as described by Ward in 1982 (M92-57).  
New BTs- 13" Fir, scribed "S14 ¼ BT", BT tag, bears;  
N.69°27'E., 17.1 ft to spike.  
14" Fir, scribed "S14 ¼ BT", BT tag, bears;  
S.54°50'E., 19.3 ft to spike.  
8" Fir, scribed "S15 ¼ BT", BT tag, bears;  
S.72°33'W., 3.8 ft to spike.  
15" Fir, scribed "S15 ¼ BT", BT tag, bears;  
N.14°59'W., 15.9 ft to spike.  
BT tags placed on new BTs., measurement from a 6" spike placed in the root collar below the face, to the corner monument.