

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 1996)

-----  
Set post corner of secs. 10, 11, 14 and 15, from which  
A Maple 24" dia., bears N.85°E., 87 lks. dist.  
A Cedar 36" dia., bears S.65°E., 150 lks. dist.  
To the West, too steep and rocky to make other bearing trees.  
Raised monument of stone.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2033-34)

-----  
Sec. Cor. post which being gone, I reestablish the same by setting an Elder post, 4 ft. long, 4" sq., 24" in the ground with a mkd. sandstone 16x10x10 ins., 12" in the ground, mkd. T22S S11 on NE.; R12W S14 on SE.; S15 on SW.; S10 on NW faces, with 4 notches on S. and 2 notches on E. edges, from which

A Maple 24" dia., bears N.85°E., 87 lks. dist. mkd. T22S R12W S11 BT.  
A Cedar 36" dia., bears S.65°E., 150 lks. dist. mkd. T22S R12W S14 BT.

in accordance with the description given in the field notes furnished me.

Survey by Richard Hintz - For: Champion International - Oct. 1978 - M 74-4

-----  
Set stamped 2" I.P. with brass cap, from which  
72" Cedar bears S.65°E., 99.0 ft. Orig. BT. Set 50d nail in new face which bears S.65°30'W., 97.7 ft. scribed.  
38" Maple N.24°30'E., 61.7 ft.  
20" Alder S.39°W., 30.1 ft.  
28" Maple N.83°W., 89.8 ft.

Fd. OK, Oct. 1984 by B.W. Holt - M 97-63