

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 1996)

Set ¼ sec. post, from which
A Cedar 12" dia., bears N.58°E., 9 lks. dist.
A Fir 60" dia., bears S.85°W., 25 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - S.A. Bilow, crew - June 3, 1959 - C.S. File 49/153-2

Found - Orig. 60" now 60" Fir stump S.85°W., 16.5 ft. previously opened, shows good scribing "4S".
I find no trace of original NE BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 22 S R 12 W
¼ S10 | S11
1959

New BTs -40" Cedar stump S.2°E., 7.0 ft. scribed ¼ S CS BT.
18" Hemlock N.80°W., 15.0 ft. scribed ¼ S10 CS BT.

Fd. OK June 1982 by Bruce Shaner - RM 3-59

Fd. OK Oct. 1984 by Burton Holt - M 97-63

Estabrook Land Surveying - For: Weyerhaeuser Co. -
5/1/2025 - M186-2

Found - 2" Brass cap on a 1½" iron pipe.
40" Cedar stump with tag bears S.02°W. 7.0'.
60" Fir stump with visible scribe in face and tag bears S.85°W. 16.5'.
24" Hemlock stump with healed face bears N.80°W. 15.0'.

New - 6" Fir, faced & scribed "XBT" with x-chop & tag bears N.68°E. 14.2 to a spike at side center.
8" Fir, faced & scribed "¼ S11 VT" with x-chop & tag bears S.73°E. 15.5' to a spike at side center.
8" Fir, faced & scribed "¼ S10 BT" with x-chop and tag bears S.42°W. 6.1' to a spike at side center.
6" Fir, faced & scribed "XBT" with x-chop and tag bears N.61°W. 8.9' to a spike at side center.

Found B0 - Steel fence post bears S.07'