

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCS0 records Vol. 5 Page(s) 1989)

Set ¼ sec. post from which
 A Fir 18" dia., bears S.18°E., 20 lks. dist.
 A Hemlock 10" dia., bears S.25°W., 11 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - For: Warren Waggoner - Aug. 9, 1956 - C.S. File 47/129

Found - 24" rotted Fir stump, orig. BT, 18" Fir S.2°E., 13.2 ft. scribed BT.
Set an iron pipe with brass cap mkd: T22S R12W ¼ S3|S2 County Surveyor's Office, 1956, from which
 10" Hemlock bears S.48°E., 10.6 ft. scribed ¼ S2 CS BT.
 8" Hemlock bears N.9°W., 19.6 ft. scribed ¼ S3 CS BT

Fd. BC/IP, Aug. 1965 by C. Stephens - M 22-71

Stephen Stys - For: Roseburg Resources Co. - 5/2023 - M182-49

Found - A 2½" brass cap set on a 1½" iron pipe, (properly mkd) 1956
Set steel post alongside corner monument
24" rotten Hemlock stump, no vis marks, bears S.48°E., 10.6'
New - A 17" Hemlock, faced & scribed "E ¼ S3 BT" with X-chop and tag bears N.2°W., 17.5' To a spike at side center.
A 14" Hemlock, faced & scribed "W ¼ S2 BT" with X-chop and tag bears N.30°E., 12.3' to a spike at side center.
A 11" Hemlock, faced & scribed "W ¼ S2 BT" with X-chop and tag bears S.53°E., 7.7' to a spike at side center.
A 8" Hemlock faced & scribed "E ¼ S3 BT" with X-chop and tag bears S.40°W., 4.7' to a spike at side center.
LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS:
N: 43°41'23.9" W: 124°06'13.5" (Not survey grade)