

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec Cor for 2 & 3; and 34, 35, T21-12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCS0 records Vol. 3 Page(s) 1264)

-----  
Set post cor. of secs. 2, 3, 34 and 35, from which  
A Crab, 4" dia., bears S.75°W., 36 lks. dist.  
A Spruce 10" dia., bears N.20°W., 65 lks. dist.  
A Spruce 12" dia., bears N.8°E., 102 lks. dist.  
A Spruce 18" dia., bears S.80°E., 458 lks. dist.

-----  
Douglas Co. Surveyors Office - James Byron, Deputy - Survey for: Warren Waggoner - Aug. 9, 1956 - C.S. File 47/129

-----  
Position of corner determined by tie (N.15°W., 253.3 ft.) shown on Amended Plat of R.R. Addition and ties made on Winchester Ave.

Set an Iron pipe with brass cap at corner point mkd:

T21S  
S 34 | S 35 R12W  
S 3 | S 2

County Surveyors Office, 1956

Blazed and scribed:

14" Cedar N.20°28'30"E., 283.83 ft. mkd. S35 T21S R12W CS  
BT.

-----  
Eugene Wobbe, surveyed for Henderson - Sept. 1996 - Partition Plat 1996-0080

-----  
Found - 5/8" iron rod 5' under ground  
- 40" Cedar, bears N.20°11'35"E., 285.03 ft.  
Set - 5/8" iron rod with yellow plastic cap marked "WOBBE-PLS 1093" at ground level.

Fd. OK by Solarz, Aug. 1998 - 1998-0097

-----  
Stephen Stys - For: Roseburg Resources Co. - 5/2023 - M182-49

-----  
Tree growing at location of section corner. Calculated by compass adjustment per partition plat 1996-0080.

Found 2 each 5/8" iron rod, as noted per partition plat 1996-0080.

Per M182-49A - (5/8" IR) N.24°45'54"E. 357.47', calculated pt  
Per 1996-0080 - 5/8" IR S.44°W., 75.63'