

PRIMARY CORNER DESCRIPTION Sec. cor. for 2 & 3 only, T23-12

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #341, dated October 4, 1879 (DCSO records Vol. 5 Page(s) 2020)

Set Crabapple post, 6x6 by 5 ft. long in ground, from which
An Alder 24" dia., bears S.61°W., 42 lks. dist.
A Willow 4" dia., bears N.46°W., 60 lks. dist.
An Alder 12" dia., bears N.32°E., 202 lks. dist.
Nothing near in Sec. 2 suitable to mark.
This post stands in a barley patch of a settler by the name of Carlson.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2030-31) and Pages 2025-26)

Cor. to secs. 2 and 3, which is a Crabapple post, 6" sq., 24" above ground, marked S35 T22S on NE.; S2 R12W on SE.; S3 T23S on SW.; S34 on NW. faces, with 2 notches on E. and 4 notches on W. edges, from which
Stump of Alder 12" dia., bears N.32°E., 202 lks. dist. mkd. BT.
Stump of Alder 24" dia., bears S.61°W., 42 lks. dist. mkd. BT.
In accordance with the description in the field notes furnished me. Destroyed marks of Secs. 34 and 35 on old post.

Survey by Ronald Stuntzner - Nov. 14, 1970 - C.S. File 55/172 (and C.S. File 58/37-4, Stuntzner 1980 survey)

Beginning at the Sec. Cor. to 2 and 3 only, We found the corner established by Stephens, referenced by a witness corner which is 167.5 ft. South along the section line of the true corner point. At witness corner, we found a 3/4" Iron pipe, from which
24" Cedar S.70°E., 61.4 ft.
18" Fir S.39°W., 28.7 ft.
I Scribe a 12" Maple S.42°E., 6.2 ft.

Fd. OK, by Lloyd D. Smith, OSBF - Dec. 1985, M 100-37 and Jan. 1986, M 100-38

Survey by Mark Hoyer, LS #2098 - For: Menasha Corp. - Nov. 1987 - C.S. File 63/65 and M 105-15

(Cont. Next Page)

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 512100

PRIMARY CORNER DESCRIPTION Sec. cor for Secs. 2 & 3 only, T23-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found - 3/4" Iron pipe. (Witness corner)
25" D.Fir S.39°W., 28.7 ft., face visible.
26" forked Maple S.44°E., 6.0 ft., scribing visible.
32" Cedar S.70°E., 61.4 ft., no scribing.
I remonument by driving a 1½" x 36" I.P. with brass cap over
existing pipe and tag the three bearing trees.