

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #323, dated May 26, 1879, - (DCSO records Vol. 5 Page(s) 2018)

Set Maple post 40" long, 5" dia., 20" in ground for the quarter section corner between Secs. 23 and 26, from which
An Alder 16" dia., bears North, 24 lks. dist.
A Cedar 60" dia., bears S.89°W., 65 lks. dist.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - March 20, 1970 - M 33-79

1/4 cor. reestablished by proportionate measurement.
Set OSBF 1½" x 36" galv. Iron pipe with 3" bronze cap, in mound of rock, from which
"X" on sandstone rock face, N.18°E., 9.7 ft., bearing object.
8" Alder S.9°W., 38.0 ft. with yellow metal location poster RS 359.
1.0 ft. creek, South 12.5 ft., course N.80°W.
4x4x72" white painted cedar post bears S.E. 2.0 ft.

Fd. OK, May 1991 - M 113-35 A&B