

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 5 Page(s) 2015)

Set post for ¼ sec. corner, from which
A Cedar 20" dia., bears S.30°W., 11 lks. dist.
A Cedar 30" dia., bears N.65°E., 20 lks. dist.

Survey by Clifford A. Stephens - For: O.B. Walker - July 14, 1966 (filed June 1968) - C.S. File 55/80 and M 38-35

Search for ¼ sec. cor. and find nothing.
Reestablish by driving a 4 ft. long, 3/4" copper pipe, 3½ ft. in the ground for the corner, from which
A D.Fir 22" dia., bears N.39°W., 45.3 ft.
A R.Cedar 10" dia., bears S.62°W., 48.7 ft. with location tag on face.
The corner is East of a high spur bearing NE. and SW., a distance of 50 ft. The 10" Red Cedar BT is on the top of the spur. It is also at the foot of a rock face on SE. slope.

Fd. OK, May 1991 by Robert Ward - M 113-35 A&B
Fd. Ok by Corey Woodruff, 2/2006 - M149-65